

DIAMONDBACK™ S



Automatic Textile Press



FEATURES

- 6-9 colors
- Maximum image area
41 x 46 cm (16" x 18")
- Standard pallet size 41 x 56 cm (16" x 22")

Most owners of manual-press operations are constantly looking for ways to justify upgrading to an automatic press because of the tremendous benefits automation offers. Entry-level automatics can dramatically increase output, giving shops the ability to take on large and last-minute jobs. They also minimize labor costs and they largely eliminate the tedium and hard physical effort involved in hand-pulling squeegees. In shops where the owner does much of the printing, an automatic's high-speed production can free up time to work with existing clients—and seek out new ones.

Unfortunately, those benefits often lost out to the cost factor—until now. By relying on simplicity of design, strong standard-feature sets, highly-efficient manufacturing processes, and volume production, M&R's Diamondback S has broken the price barrier between you and your first automatic. The Diamondback S features a fast, reliable servo index drive system, and is available in 6 and 8-color models, with a maximum image area of 41 x 46 cm

(16" x 18") and a maximum pallet size of 46 x 56 cm (18" x 22"). Diamondback S can be ordered with an additional printhead over the unload station, turning the 6-color into a 7-color and the 8-color into a 9-color.

Diamondback S is available in base and enhanced configurations. Both models feature pneumatically-driven print carriages, swiveling control panel arm with touch-screen display, micro-registration, calibrated squeegee pressure adjustment, standard M&R three-point pallet leveling bracket with quick release, and rear stroke length adjustment. M&R's exclusive patented Revolver Print Program™ automatically operates individual printheads in programmed sequence and allows multiple flashing without losing a printing position, giving printers a level of flexibility unavailable on other presses. Enhanced Diamondback S models add pneumatic frame locks, pneumatic squeegee/floodbar locks, and pneumatic squeegee pressure regulators. If you've been waiting for the right price on an entry-level automatic, your wait is over.

www.mrprint.com
store.mrprint.com

DIAMONDBACK™ S

STANDARD FEATURES

CAROUSEL/INDEXER

- Clockwise or counterclockwise rotation

CENTRAL OFF-CONTACT

- Permits fast, incremental single-lever adjustment of all stations simultaneously

CONTROL CENTER

- Countdown program indicates when operator-set index count has been reached
- Independent print-start/print-finish setting automatically activates and stops printheads at the beginning and end of production runs
- Multiple (1-9) print stroke capability
- Multi-print in the up position
- Onboard self-diagnostics
- Real-time production data
- Swiveling control arm with touch-screen display

INDEX SYSTEM

- Servo-driven index ensures accurate, smooth travel

PALLET SYSTEM

- Precise three-point pallet leveling system
- Tool-free pallet locator speeds pallet changeover
- Tool-free quick release pallet locks

PRINTHEADS

- Four-point off-contact adjustment
- Independent print/flood speed controls on each printhead simplify press setup
- Pneumatically-driven printheads

REGISTRATION

- Compatible with M&R's Tri-Loc® & Double Tri-Loc® Rapid Registration Systems
- Enhanced micro-registration adjustments with visual guides

REVOLVER PRINT PROGRAM

- Automatically operates individual printheads in programmed sequence and allows multiple flashing without losing a printing position (U.S. Patent No. 5,595,113)

SCREEN CLAMPS & HOLDERS

- Adjustable side clamps accommodate a wide variety of screen sizes
- Clamping system holds roller frames without special adapters
- Manual clamps hold frames tight and allow rapid screen loading (pneumatic clamps on enhanced models)

SQUEEGEE/FLOODBAR

- Angle and calibrated pressure adjustments are independently set
- Front or rear print carriage stop position allows operator to leave screens clear or flooded (great for water-based inks)
- Independent squeegee & floodbar speed adjustments
- Manual squeegee pressure regulators (pneumatic pressure regulators on enhanced models)
- Manual squeegee/floodbar clamps (pneumatic clamps on enhanced models)
- Visual reference marks every 5 degrees simplify squeegee/floodbar angle adjustments

STROKE LENGTH ADJUSTMENT

- Adjustable rear stroke length with tool-free adjustment maximizes print speed

WARRANTY, SERVICE AND SUPPORT

- 24-hour hotline is staffed 365 days a year
- Access to M&R's Training Center
- Parts & supplies are available online at store.mrprint.com
- Two-year limited warranty

OPTIONS

DESIGN & CONSTRUCTION

- Designed & disassembled to fit through a 78 cm (31") doorway

FOOT PEDAL CONTROL

- Allows indexing of the press using a foot pedal
- Skip-pallet feature allows operators to avoid printing empty pallets

OPTICAL NO-SHIRT DETECTOR

- Automatically prevents the press from printing on empty pallets (U.S. Patent No. 5,383,400)
- Reduces misprints and minimizes press stoppage because of improperly loaded shirts

PRINTHEADS

- Additional printhead for placement at the unload station turns the 6-color into a 7-color and the 8-color into a 9-color (also available for retrofit)
- Enhanced printhead option includes pneumatic squeegee/floodbar clamps with tool-free angle adjustment, pneumatic screen frame clamps, and pneumatic squeegee pressure regulators with pressure gauges

SPECIFICATIONS

	Diamondback S 8/6	Diamondback S 8/7	Diamondback S 10/8	Diamondback S 10/9
Air @ 6,9 Bar (100 psi)	566 l/min (20 cfm)	651 l/min (23 cfm)	765 l/min (27 cfm)	850 l/min (30 cfm)
Diameter	328 cm (10' 9")	328 cm (10' 9")	373 cm (12' 3")	373 cm (12' 3")
Electrical Requirements ¹	208/230 V, 1 ph, 5 A, 50/60 Hz, 1.15 kW 110 V, 1 ph, 10 A, 50/60 Hz, 1.15 kW	208/230 V, 1 ph, 5 A, 50/60 Hz, 1.15 kW 110 V, 1 ph, 10 A, 50/60 Hz, 1.15 kW	208/230 V, 1 ph, 5 A, 50/60 Hz, 1.15 kW 110 V, 1 ph, 10 A, 50/60 Hz, 1.15 kW	208/230 V, 1 ph, 5 A, 50/60 Hz, 1.15 kW 110 V, 1 ph, 10 A, 50/60 Hz, 1.15 kW
Maximum Frame Size	58 x 84 x 4.5 cm (23" x 33" x 1.75")	58 x 84 x 4.5 cm (23" x 33" x 1.75")	58 x 84 x 4.5 cm (23" x 33" x 1.75")	58 x 84 x 4.5 cm (23" x 33" x 1.75")
Maximum Image Area	41 x 46 cm (16" x 18")	41 x 46 cm (16" x 18")	41 x 46 cm (16" x 18")	41 x 46 cm (16" x 18")
Shipping Weight	1415 kg (3120 lb)	1483 kg (3270 lb)	1656 kg (3650 lb)	1724 kg (3800 lb)
Standard Pallet Size	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22")
Stations/Colors	8/6	8/7	10/8	10/9

¹ If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly. Other electrical configurations are available. Contact The M&R Companies for details.



The M&R Companies
M&R • NUARC • AMSCOMATIC

M&R Sales and Service, Inc. 1N372 Main Street, Glen Ellyn, Illinois 60137-3576 USA

USA: 800-736-6431 / 630-858-6101 / Fax: 630-858-6134 • Outside USA: +1 847-967-4461 / Fax: +1 847-967-0417

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2012 M&R Printing Equipment, Inc. All rights reserved. 011712