

## Automatic Screen Cleaning and Reclaiming System



### FEATURES

- Automates and simplifies one of the least-desirable aspects of the screen printing process
- Recirculates screen-cleaning chemicals to reduce environmental impact and lower operating costs
- Stainless-steel construction ensures long life and minimal maintenance

M&R's Eco-TEX automates and simplifies the entire screen-cleaning process, and it handles screens up to 132 x 97 cm (52" x 38"). In the process, Eco-TEX reduces environmental impact and lowers operating costs by recirculating screen-cleaning chemicals. Users have the option of removing ink while leaving the emulsion intact, or of completely stripping ink, emulsion, and other residue from screens. Once screens have been cleaned, Eco-TEX rinses them with a high-pressure fresh-water power wash. Power-washing both sides of the screen simultaneously accelerates the cleaning process. The entire procedure takes place in a single automatic cycle—and in a single chamber. An electric conveyor sends dirty screens into the chamber and clean screens out. Solvents are automatically pumped back to the holding tank after each cleaning cycle, reducing chemical use and lowering the cost of operation.

Eco-TEX is also modular. An additional chamber can be added to handle ink washing in one chamber and screen reclaiming in the other. The two-chamber approach greatly increases production capacity. A single-chamber Eco-TEX can clean up to 100 screens per shift (based

on two screens per cycle). A dual-chamber version can nearly double that figure. In addition, a specially-designed stainless-steel chase holds up to fifteen squeegee holders, flood bars, or spatulas, allowing Eco-TEX to automatically take care of this otherwise labor-intensive process. The easy-to-clean Eco-TEX filtration system prevents foreign matter from contaminating cleaning chemicals and jet nozzles. Eco-TEX has no external moving parts, and it eliminates direct employee exposure to the cleaning process. It's economical to operate, and it helps shops keep screen-cleaning/reclaiming areas clean.

Eco-TEX offers user-friendly touch-screen control over all operations, and includes complete self-diagnostic functionality. The machine's compact footprint makes it easy to place in almost any shop, and its reversible conveyor allows right-to-left or left-to-right movement, expanding options for machine placement. Stainless-steel construction minimizes maintenance and ensures a long, productive life. Low operating costs, versatile design features, and competitive pricing make Eco-TEX the ideal addition to any screen-printing operation.

## STANDARD FEATURES

### CERTIFICATION

- CE & UL compliant: Built to specifications established by the European Committee for Standardization® (CE) and Underwriters Laboratories® (UL)

### CONTROL CENTER

- Digital touch-screen control panel with onboard self-diagnostics controls all machine functions

### DESIGN & CONSTRUCTION

- All stainless-steel construction
- Modular design allows future expansion

### SCREEN LOADING

- Automatic screen loading and unloading simplifies operation

### WARRANTY, SERVICE AND SUPPORT

- 24-hour hotline is staffed 365 days a year
- Access to M&R's Training Center
- Parts & supplies are available online at [store.mrprint.com](http://store.mrprint.com)
- One-year limited warranty



## OPTIONS AND ACCESSORIES

### DESIGN & CONSTRUCTION

- Second cleaning chamber enables higher throughput

### SCREEN WASHING & RECLAIMING CHEMICALS

- Eco-Reclaim strips stencil (emulsion)
- Eco-Wash cleans ink residue out of the screens
- M&R's proprietary chemicals are designed and optimized for use with Eco-TEX

## SPECIFICATIONS

	ECO-TEX
Air @ 6 bar (87 psi)	850 l/min (30 cfm)
Electrical Requirements <sup>1</sup>	208/230 V, 3 ph, 35 A, 50/60Hz, 7 kW 380/415 V, 3 ph, 19 A, 50/60 Hz, 7 kW
Exhaust Requirements <sup>2,3</sup>	15.2 cm (6")- 8498 l/min (300 cfm) @ 6 mm (1/4")
Maximum Screen Frame Size <sup>4</sup>	132 x 97 x 5 cm (52" x 38" x 2")
Overall Size (L x W x H)	640 x 117 x 224 cm (252" x 46" x 88")
Shipping Weight	681 kg (1500 lb)

<sup>1</sup> If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly. Other electrical configurations are available: Contact The M&R Companies for details.

<sup>2</sup> Measured at the Exhaust Discharge Port

<sup>3</sup> Static pressure

<sup>4</sup> Custom configurations may be available: Contact The M&R Companies for details.



**The M&R Companies**  
M&R • NUARC • AMSCOMATIC

**M&R Sales and Service, Inc. 1N372 Main Street, Glen Ellyn, Illinois 60137-3576 USA**

**USA: 800-736-6431 / 630-858-6101 / Fax: 630-858-6134 • Outside USA: +1 847-967-4461 / Fax: +1 847-967-0417**

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2011 M&R Printing Equipment, Inc. All rights reserved. 090111