

K-840™ & K-895™



Automatic Folding Systems

FEATURES

- Dual-belt transport system dramatically improves folding performance
- Parallel-adjusting fold plates ensure clean, straight folds
- Timing belt drive system for smooth, quiet operation



K-895 with optional L-15HPA Print/Apply Labeler

Amscomatic's K-840 and K-895 are sophisticated high-speed automatic folding systems designed to precisely fold a wide variety of garments and other textile items. They're engineered for dependable performance and low maintenance in demanding, high-production environments, and can be easily integrated with other Amscomatic equipment into automatic folding/bagging/sealing systems. A significant technological breakthrough—M&R's patented bottom pulling dual-belt (upper and lower) transport system—finally makes it possible to fold garments printed with high density or gel inks.

Folding plates electronically adjust to the desired width while staying parallel to each other. This allows tighter, more consistent folding on all types of products. Wide transfer belts in the second-fold area minimize maintenance and improve performance. The entire garment

transport system uses a timing belt drive, which runs quieter and requires less long-term maintenance than chain & sprocket drives.

Top covers of Plexiglas and extruded aluminum provide clear views and easy access to components from both sides of the folder. Quick-release side panel covers allow easy access to the inner workings of the machine. All covers are interlocked, ensuring that the machine will not operate when a cover has been loosened or removed. K-840 folding adjustments are made using the dials and switches on the control panel. The K-895's touch-screen user interface allows users to quickly change fold sizes. It also allows K-895 users to store up to 99 fold settings for quick changeover. Both machines can be combined with various styles of label applicators and printers, further improving productivity.

www.amscomatic.com

USA: 800-736-6431 • Outside USA: +847-967-4461



K-840™ & K-895™

STANDARD FEATURES

Certification

- CE & UL compliant: Built to specifications established by the European Committee for Standardization® (CE) and Underwriters Laboratories® (UL)

Control Center

- Electronic cycle counter for production rate tracking
- Fold parameters are changed electronically
- LCD touchpad interface controls most machine parameters (K-895)
- PLC (programmable logic control)
- Servo-driven fold plate and tucker plate mechanisms (K-895)
- Stores up to 99 fold settings into memory (K-895)

Cycle Sensors

- Choice of Finger (Opto-Eye) Sensor or Shirt (Speed-Eye) automatic loading sensor
- Finger (Opto-Eye) Sensor allows more time for loading garments that are difficult to place properly on the drape table
- Shirt (Speed-Eye) Sensor increases production by automatically initiating the folding cycle when a sensor determines that a garment is in position on the drape table

Design & Construction

- Bottom Pulling Belt (U.S. Patent No. 6,913,171) makes it possible to fold garments printed with high density or gel inks
- Circuit breakers protect the electrical panel
- Interlocking system displays a "cover open" message when any cover has been opened or removed
- Parallel fold plates offer the ultimate in folding performance
- Side panel covers have quick-release latches
- Top covers of Plexiglas and extruded aluminum provide excellent visibility and allow access from both sides of the folder
- Unitized frame

Fold Width

- Additional fold plate sizes expand folder capability
- Adjusts to different size products
- Standard fold plate width is 13 to 23 cm (5" to 9")

Infeed System

- Drape Table

Warranty, Service and Support

- 24-hour hotline is staffed 365 days a year
- Access to M&R's Training Center
- One-year limited warranty

OPTIONS

Cycle Sensors

- Finger (Opto-Eye) Sensor + Shirt (Speed-Eye) Sensor combination offers the ultimate in versatility

Design & Construction

- Heavy-duty casters for easy mobility

Fold Plates

- 18 to 33 cm (7" to 13")

Split-Belt

- For garments with buttons, zippers, or plackets

SPECIFICATIONS

	K-840	K-895
Air @ 5,5 bar (80 psi)	85 l/min (3 cfm)	85 l/min (3 cfm)
Electrical Requirements ¹	110 V, 1 ph, 8.4 A, 50/60 Hz, 1 kW 208/230 V, 1 ph, 4.2 A, 50/60 Hz, 1 kW	110 V, 1 ph, 9.8 A, 50/60 Hz, 1.1 kW 208/230 V, 1 ph, 4.9 A, 50/60 Hz, 1.2 kW
Shipping Weight	817 kg (1800 lb)	817 kg (1800 lb)
Size (L x W x H)	356 x 81 x 130 cm (140" x 32" x 51")	356 x 81 x 130 cm (140" x 32" x 51")

¹ If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly. Other electrical configurations are available. Contact The M&R Companies for details.



The M&R Companies
M&R • NUARC • AMSCOMATIC

The M&R Companies 1N372 Main Street, Glen Ellyn, Illinois 60137-3576 USA

USA: 800-736-6431 / 630-858-6101 / Fax: 630-858-6134 • Outside USA: +1-847-967-4461 / Fax: +1-847-967-0417

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2008 M&R Printing Equipment, Inc. All rights reserved. 050708