Pre-Press Accessories

Max Newton[™] Screen Stretching System

M&R's economical pneumatic screen stretcher delivers high-tension stretching on virtually any mesh/frame combination. Max Newton's air cylinders compensate for variations in mesh elasticity and fully extend after tensioning. Warp and weft are independently tensioned and controlled, and the durable PVC-coated locking bars grip tightly without tearing mesh. Economical and easy to use, Max Newton is a great addition to any screen printing operation.



Turnabout[™] Automatic Ink Mixer

The Turnabout automatic ink mixer employs a blade that imparts a lifting and rolling action to screen printing inks. That, coupled with Turnabout's rotating action, ensures evenly blended inks, even reaching ink that typically settles on the sides and bottoms of containers. The container clamping system is self-centering and adjusts to accommodate a wide range of container sizes. Turnabout HD, driven by an AC electric variable-speed motor with constant torque, is designed for use with thicker, more viscous screen printing inks and coatings like high-density plastisol. It rotates counterclockwise. Turnabout DC has variable speed and rotates clockwise or counterclockwise.

Container Size Capacity 4-20 liter (1-5 gallon) 20 liter (5 gallon)	
- contained experiency - contain (a gaineir)	
Electrical Requirements 1 110 V, 1 ph, 5 A, 50/60 Hz, 0.6 kW 110 V, 1 ph, 6 A, 50/60 UZ 08/230 V, 1 ph, 2 A, 50/60 Hz, 0.5 kW	
Shipping Weight 68 kg (150 lb) 68 kg (150 lb)	

If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly Other electrical configurations are available: Contact The M&R Companies for details.

BladeShaper[™] Squeegee Sharpeners

Precisely sharpened squeegee blades are essential to high-quality prints, and M&R offers BladeShaper squeegee sharpeners for virtually every requirement. BladeShaper SC sharpens blades up to 51 cm (20") long, and BladeShaper MC sharpens blades up to 97 cm (38") long. Both are compact, easy to move, and fit almost anywhere.

M&R's freestanding, midsize, fully-automated BladeShaper LC precisely sharpens blades up to 95 cm (37") long. It's ideal for busy shops because the operator does not need to remain with the machine during the sharpening process. Grinding wheels in seven different profiles are available for all models. Detailed information on each sharpening system is available at the M&R website.





M&R · NUARC · AMSCOMATIC

The M&R Companies 1N372 Main Street, Glen Ellyn, Illinois 60137-3576 USA USA: 800-736-6431 / 630-858-6101 / Fax: 630-858-6134 • Outside USA: +1-847-967-4461 / Fax: +1-847-967-0417

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for dimanges, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2014 M&R Printing Equipment, Inc. All rights reserved. 20140825

On-Press Accessories

Annamister Jr.™

Manual Adhesive Application System

Annamister Jr. is a convenient, highlyaffordable alternative to inconvenient, costly aerosol cans. It allows operators to quickly and easily apply a fine coating of waterbased adhesive to screen printing pallets and platens. The fully-adjustable spray jet provides precise and consistent one-handed adhesive application. Compact and portable, the sturdy, height-adjustable floor stand can be easily rolled into place, and it includes a submersible pump and a shelf for a 20 liter (5 gallon) bucket.

Annamister Jr. requires 85 l/min (3 cfm) of air @ 2,8 bar (40 psi). Shipping weight is 27 kg (60 lb). Annamister Jr. is the ideal pallet adhesive application system for manual and automatic screen printing presses.

Quik-Klamp Squeegee Clamping System

M&R's Qwik-Klamp modular squeegee clamping system makes it a snap to assemble and disassemble squeegee holders and blades up to 56 cm (22"). And the modular base unit can be joined with one or more expansion units to enable clamping squeegee holders and blades of virtually any practical length, making Qwik-Klamp ideal for squeegees used in Graphics printing and in oversize and all-over T-shirt printing. See M&R's Qwik-Klamp brochure for complete details.



Kool-Mist[™]

After-Flash Cool-Down Unit


Kool-Mist automatically cools down screen prints and minimizes after-flash tack by applying a highpressure atomized spray of water and food-grade silicone. Positioning Kool-Mist between the flash cure unit and the next printhead eliminates the need for an open station. A single proximity switch and mounting bracket make it easy to integrate Kool-Mists with screen printing presses. Digital programmable controls make Kool-Mist easy to operate.

Compact and portable, the sturdy, height-adjustable floor stand can be easily rolled into place, and it includes a submersible pump and a shelf for a 20 liter (5 gallon) bucket.

Kool-Mist requires 110 V, 1 ph, 5 A, 50/60 Hz, .2 kW and 85 l/min (3 cfm) @ 6,9 bar (100 psi). Shipping weight is 46 kg (100 lb).

Squeegee Blades

M&R features a wide variety of premium textile squeegee blades: Single-layer blades in 65, 75 & 85 durometer; sandwiched triple-layer blades in 65/90/65 and 75/90/75 durometer; and double-bevel blunt



blades in 80 durometer. All blades are color coded and labeled with part numbers, sharpen-to lines, and batch numbers. They're sold by the inch or in full 365 cm (144") rolls. No minimum order is required. Sandwiched triple blades offer a stiffer 90-durometer center section for squeegee rigidity, and softer 65 or 75-durometer printing edges on the outside. Since the more rigid center section helps keep the squeegee from hydroplaning over the ink and bending, operators get the ink-depositing characteristics of softer blades without compromising press speed.

Squeegee Holders & Floodbars

M&R carries squeegee holders and floodbars in a clear anodized finish. Durable and dependable, all M&R squeegee holders and floodbars stand the test of time.



Winged Floodbars

