

## UV LED Screen Print Curing System And Conveyor Dryer



M&R's Photon is the finest UV LED cure system available, and it represents a revolutionary advance over ferric/iron oxide, gallium, and mercury vapor light sources. Photon's UV LEDs run cool (very little heat is transferred to substrates), consume less power, last longer (up to 25,000 hours), and increase conveyor belt longevity. Photon's sheet sensor automatically turns LEDs on and off to further reduce power consumption. A powerful turbine holds down even lightweight substrates while the chamber is air cooled. LED temperature output is so low that cooling can be provided by the building's ambient air. Since Photon's UV LEDs run cool and generate no ozone, heating and cooling costs are reduced and exhaust air doesn't have to be vented outside. And since it has no reflectors or rotating lamps, Photon is easier to clean and maintain.

Photon's variable-frequency AC-drive motor powers M&R's Teflon-coated fiberglass Patriot Belt™ with the SureTrak™ roller system (U.S. Patents Pending: SN 15194035 & 15265538). The red flexible bead stitched along one edge of the Patriot Belt rides in grooves machined into the large anodized aluminum SureTrak rollers. It's the most precise dryer belt tracking available.

## FEATURES

- UV LED array runs cool, consumes less power, lasts longer, and increases conveyor belt longevity
- The finest UV LED screen printing conveyor dryer for graphics
- Belt widths from 61 cm to 183 cm (24" to 72")

Photon employs a touchscreen control panel with fully integrated PLC control to access lamp settings, belt speed, timers, maintenance reminders, programming, and system status messages. Quick tool-free adjustments accommodate varying material thickness. Hinged housings provide easy access to internal components.

Find more information and where to buy at: [www.mrprint.com](http://www.mrprint.com)



# Photon™ UV LED

## Economical Curing • Energy Efficient • Long Lamp Life

Photon's UV LEDs run cool, consume less power, last longer, and increase conveyor belt longevity. And since it has no reflectors or rotating lamps, Photon is easier to clean and maintain.



*User-friendly touchscreen interface provides ease of use*



*Sheet sensor turns LEDs on and off automatically to save power*

# COOL

## CURING CONVEYOR!

*Photon's sheet sensor automatically turns LEDs on and off to further reduce power consumption. LED temperature output is so low that cooling can be provided by the building's ambient air. Since the UV LEDs run cool and generate no ozone, exhaust does not need venting.*

SPECIFICATIONS	Photon 24-10	Photon 30-10	Photon 38-10	Photon 48-10	Photon 54-15	Photon 60-15	Photon 72-15
<b>Belt Length</b>	305 cm (10')	305 cm (10')	305 cm (10')	305 cm (10')	457 cm (15')	457 cm (15')	457 cm (15')
<b>Electrical Requirements<sup>1</sup></b>	208/230 V, 1 ph, 44/40 A, 50/60 Hz, 6.1 kW	208/230 V, 1 ph, 53/48 A, 50/60 Hz, 7.8 kW	208/230 V, 1 ph, 53/48 A, 50/60 Hz, 7.8 kW	208/230 V, 1 ph, 63/57 A, 50/60 Hz, 9.4 kW	208/230 V, 1 ph, 63/57 A, 50/60 Hz, 9.5 kW	208/230 V, 1 ph, 73/66 A, 50/60 Hz, 11.1 kW	208/230 V, 1 ph, 82/75 A, 50/60 Hz, 12.8 kW
<b>LED &amp; Belt Width</b>	61 cm (24")	76 cm (30")	97 cm (38")	122 cm (48")	137 cm (54")	152 cm (60")	183 cm (72")
<b>Shipping Weight</b>	635 kg (1400 lb)	680 kg (1500 lb)	726 kg (1600 lb)	816 kg (1800 lb)	953 kg (2100 lb)	1043 kg (2300 lb)	1270 kg (2800 lb)

<sup>1</sup> If incoming voltage differs from the voltage(s) listed in the brochure, calculate amperage accordingly. Other electrical configurations are available. Contact The M&R Companies for details.

**M&R Sales and Service, Inc.** 440 Medinah Road, Roselle, Illinois 60172-2329 USA [www.mrprint.com](http://www.mrprint.com)  
**USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • FAX: 630-858-6134**

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2019 M&R Printing Equipment, Inc. All rights reserved. 20190530