

Direct to Film (DTF) Transfer Printing System**INDUSTRIAL
COMPONENTS****FAST PRINT
PRODUCTION****VIBRANT
COLOR OUTPUT****CMYK+WHITE
INK SET**

*M&R QUATRO 44™ pictured with
M&R QUATRO CUTTER X™
(sold separately)*

The M&R QUATRO 44™ Direct to Film (DTF) Transfer Printing System is a modern and efficient method of applying vibrant, high-quality durable images onto a wide variety of garments, and fabric types. The DTF process begins with the creation of a digital design on a computer. Once the design is finalized, it is printed onto a special PET film with a specialized digital inkjet printer using Cyan, Magenta, Yellow, Black and White pigmented aqueous inkjet inks. After printing is complete, and while the ink is still wet, the transfer is prepared by applying a layer of adhesive to the print area.

Immediately after the adhesive has been applied, the final construction of film, ink, and adhesive is prepared for the transfer process by running it through a high efficiency infrared drying system to cure the ink, and to fuse the adhesive to achieve a strong bond between the ink and the fabric, ensuring a durable and long-lasting print.

FEATURES

- Vibrant, high-quality prints with excellent color accuracy and sharp details
- Compatible with a wide range of fabrics, including cotton, polyester, blends, spandex and nylon
- Requires less than 200 ft² of production space with only a single operator needed

The garment is placed on a heat press and lightly pressed to remove excess moisture and to ensure that the fabric is transfer receptive. The film transfer is then laid on top of the garment in the correct alignment. The heat press is used to apply both heat and pressure, which activates the adhesive and causes the design to transfer from the film onto the fabric. The heat and pressure also ensure that the ink penetrates deeply into the fabric fibers, resulting in vibrant and vivid colors.

Find more information and where to buy at: **www.mrprint.com**

**QUATRO**
44

QUATRO 44 High-Resolution Industrial Inkjet Printer comes with:

- PC workstation with intuitive Graphic User Interface (GUI) and QUATRO RIP software - powered by CALDERA
- 4 x Epson i3200 print heads: 2 x CMYK and 2 x White
- Bulk ink system with white ink recirculation
- Print resolution (DPI), number of passes, and print production speeds:
 - 720 x 1800 DPI, 6-Pass, 90 Linear ft/hr
 - 720 x 2400 DPI, 8-Pass, 60 Linear ft/hr

QUATRO 44 Combination Adhesive Application System and Quartz Infrared Dryer includes:

- On-board bulk powder adhesive reservoir to promote continuous system operation
- Two base-mounted trays to capture excess powder adhesive for reuse
- Integrated exhaust filtration system
- Continuous temperature monitoring
- M&R's "Positive Link System" to ensure accurate film tracking between QUATRO printer, powder applicator and dryer

QUATRO 44 System Consumables

- QUATRO Inks are a joint development of M&R and our technology partner. All inks are manufactured in the United States to ISO 9001 quality standards.
- QUATRO PET Transfer Films and Powder Adhesives were selected after extensive testing to provide a cohesive ecosystem to ensure quality.
- QUATRO system purchase includes a startup kit of DTF print consumables (inks, powder and film).

M&R'S PARTNERSHIP POWER

M&R's partnership with our
ink delivery system manufacturer

M&R's partnership with our
ink and consumables manufacturer

M&R's years of dedicated
hardware, system and technical support



*4 x Epson i3200 print heads;
2 x for CMYK and 2 x for White*

| QUATRO 44 TECHNICAL SPECIFICATIONS | | Environmental Work Room Temperature | 60 – 80°F (15.6 – 26.7°C) |
|------------------------------------|--|--|--------------------------------------|
| Print Heads | 4 x Epson i3200 Print Heads — 2 x CMYK, 2 x White | Environmental Work Room Humidity | 40 – 60% |
| Print Resolution and Speed | 720 x 1800 DPI, 6-Pass, 90 Linear Feet/Hour 720 x 2400 DPI, 8-Pass, 60 Linear Feet/Hour | GENERAL SPECIFICATIONS | |
| Color Mode | CMYK and White | Electrical Requirements (Printer and Dryer) ¹ | 230 V, 1 ph, 34 A, 50/60 Hz, 8 kW |
| Ink System | White Ink Auto Circulation Supply System | Printer Dimensions (L x W x H) | 72 x 187 x 146 cm (28" x 74" x 57") |
| Ink Type | Eco-Friendly Water Based Ink | Dryer Dimensions (L x W x H) | 187 x 112 x 103 cm (74" x 44" x 40") |
| Printing Media | M&R QUATRO DTF 24" PET Transfer Film (23.8" W x 328' L) | Required Minimum Work Space (L x W) | 304.8 x 243.84 cm (10' x 8') |
| Media Transmission | Automatic Roll Out and Film Take Up | Recommended Work Space (L x W) | 365.76 x 304.8 cm (12' x 10') |
| Interface | Computer and Operating Software Included | Printer Shipping Weight | 397 kg (876 lb) |
| Included RIP Software | QUATRO RIP - powered by CALDERA | Dryer Shipping Weight | 542 kg (1196 lb) |

¹ If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly.

M&R Printing Equipment, Inc. 440 Medinah Road, Roselle, Illinois 60172-2329 USA **www.mrprint.com**
USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • FAX: 630-858-6134

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2025 M&R Printing Equipment, Inc. All rights reserved. 20250210

Direct to Film (DTF) Transfer Printing System**INDUSTRIAL
COMPONENTS****FAST PRINT
PRODUCTION****6 PRINT HEADS,
8 COLORS****CMYK, VRGO +
WHITE INK SET**

The M&R QUATRO 68™ Direct to Film (DTF) Transfer Printing System is a modern and efficient method of applying vibrant, high-quality durable images onto a wide variety of garments and fabric types. The DTF process begins with the creation of a digital design on a computer. Once the design is finalized, it is printed onto a special PET film with a specialized digital inkjet printer using Cyan, Magenta, Yellow, Black, Violet, Red, Green, Orange and White pigmented aqueous inkjet inks. After printing is complete, and while the ink is still wet, the transfer is prepared by applying a layer of adhesive to the print area.

Immediately after the adhesive has been applied, the final construction of film, ink, and adhesive is prepared for the transfer process by running it through a high efficiency infrared drying system to cure the ink, and to fuse the adhesive to achieve a strong bond between the ink and the fabric, ensuring a durable and long-lasting print.

FEATURES

- 6 x Epson i3200 print heads: 2 x CMYK, 2 x VRGO and 2 x White
- Vibrant, high-quality prints with excellent color accuracy and sharp details
- Compatible with a wide range of fabrics, including cotton, polyester, blends, spandex and nylon

The garment is placed on a heat press and lightly pressed to remove excess moisture and to ensure that the fabric is transfer receptive. The film transfer is then laid on top of the garment in the correct alignment. The heat press is used to apply both heat and pressure, which activates the adhesive and causes the design to transfer from the film onto the fabric. The heat and pressure also ensure that the ink penetrates deeply into the fabric fibers, resulting in vibrant and vivid colors.

Find more information and where to buy at: **www.mrprint.com**



QUATRO 68 High-Resolution Industrial Inkjet Printer comes with:

- PC workstation with intuitive Graphic User Interface (GUI) and QUATRO RIP software - powered by CALDERA
- 6 x Epson i3200 print heads: 2 x CMYK, 2 x VRGO and 2 x White
- Bulk ink system with white ink recirculation
- Print resolution (DPI), number of passes, and print production speeds:
 - 720 x 1800 DPI, 6-Pass, 90 Linear ft/hr
 - 720 x 2400 DPI, 8-Pass, 60 Linear ft/hr

QUATRO 68 Combination Adhesive Application System and Quartz Infrared Dryer includes:

- On-board bulk powder adhesive reservoir to promote continuous system operation
- Two base-mounted trays to capture excess powder adhesive for reuse
- Integrated exhaust filtration system
- Continuous temperature monitoring
- M&R's "Positive Link System" to ensure accurate film tracking between QUATRO printer, powder applicator and dryer

QUATRO 68 System Consumables

- QUATRO Inks are a joint development of M&R and our technology partner. All inks are manufactured in the United States to ISO 9001 quality standards.
- QUATRO PET Transfer Films and Powder Adhesives were selected after extensive testing to provide a cohesive ecosystem to ensure quality.
- QUATRO system purchase includes a startup kit of DTF print consumables (inks, powder and film).

M&R'S PARTNERSHIP POWER

M&R's partnership with our
ink delivery system manufacturer

M&R's partnership with our
ink and consumables manufacturer

M&R's years of dedicated
hardware, system and technical support



**6 x Epson i3200 print heads;
2 x for CMYK, 2 x for VRGO and
2 x for White**

| QUATRO 68 TECHNICAL SPECIFICATIONS | | Environmental Work Room Temperature | 60 – 80°F (15.6 – 26.7°C) |
|------------------------------------|--|--|--------------------------------------|
| Print Heads | 6 x Epson i3200 Print Heads — 2 x CMYK, 2 x VRGO and 2 x White | Environmental Work Room Humidity | 40 – 60% |
| Print Resolution and Speed | 720 x 1800 DPI, 6-Pass, 90 Linear Feet/Hour 720 x 2400 DPI, 8-Pass, 60 Linear Feet/Hour | GENERAL SPECIFICATIONS | |
| Color Mode | CMYKVRGO and White | Electrical Requirements (Printer and Dryer) ¹ | 230 V, 1 ph, 34 A, 50/60 Hz, 8 kW |
| Ink System | White Ink Auto Circulation Supply System | Printer Dimensions (L x W x H) | 72 x 200 x 146 cm (28" x 79" x 57") |
| Ink Type | Eco-Friendly Water Based Ink | Dryer Dimensions (L x W x H) | 187 x 112 x 103 cm (74" x 44" x 40") |
| Printing Media | M&R QUATRO DTF 24" PET Transfer Film (23.8" W x 328' L) | Required Minimum Work Space (L x W) | 304.8 x 243.84 cm (10' x 8') |
| Media Transmission | Automatic Roll Out and Film Take Up | Recommended Work Space (L x W) | 365.76 x 304.8 cm (12' x 10') |
| Interface | Computer and Operating Software Included | Printer Shipping Weight | 430 kg (950 lb) |
| Included RIP Software | QUATRO RIP - powered by CALDERA | Dryer Shipping Weight | 562 kg (1240 lb) |

¹ If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly.

M&R Printing Equipment, Inc. 440 Medinah Road, Roselle, Illinois 60172-2329 USA **www.mrprint.com**
USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • FAX: 630-858-6134

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2025 M&R Printing Equipment, Inc. All rights reserved. 20250401