



ARTISTRTM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ARTISTRTM P5400+ BLACK TEXTILE INK
 MSDS Number : 130000129166

Product Use : Printing ink
 Manufacturer : DuPont
 1007 Market Street
 Wilmington, DE 19898

Product Information : 1-302-774-1000
 Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)
 Transport Emergency : CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Potential Health Effects

Skin : May cause skin irritation. Discomfort, itching, redness, or swelling.

Eyes : May cause eye irritation. Tearing, redness, or discomfort.

Inhalation : May cause irritation of respiratory tract.

Ingestion : May cause: Central nervous system depression

Repeated exposure : Adverse effects from repeated dermal exposure may include:, Kidney effects

Target Organ : Central nervous system, Kidney

Carcinogenicity

Material	IARC	NTP	OSHA
Carbon black	2B		
Ethane-1,2-diol	: DuPont has classified this material as a probable human carcinogen.		

**ARTISTRI™ P5400+ BLACK TEXTILE INK**

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Ethane-1,2-diol	107-21-1	<10 %
Alkyl ether		<10 %
Carbon black	1333-86-4	<10 %
Cyclic amide		<10 %
Non regulated ingredients		>49%

Any component not specifically identified is considered a trade secret. Properties and potential hazards of any trade secret component are included in this safety data sheet.

SECTION 4. FIRST AID MEASURES

- Skin contact : Wash off immediately with plenty of water. Wash contaminated clothing before re-use. Get medical attention if irritation develops and persists.
- Eye contact : Immediately flush eye(s) with plenty of water. Seek medical advice.
- Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
- Ingestion : Is not considered a potential route of exposure. If swallowed Do NOT induce vomiting. Call a physician or poison control centre immediately.

**ARTISTRI™ P5400+ BLACK TEXTILE INK**

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

SECTION 5. FIREFIGHTING MEASURES

Flammable Properties

Flash point : 93 °C (199 °F)

Fire and Explosion Hazard : Not a fire or explosion hazard. Cool closed containers exposed to fire with water spray.

Suitable extinguishing media : Not combustible.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Keep containers and surroundings cool with water spray.

Firefighting Instructions : Immediately evacuate personnel to safe areas. Wear suitable protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Cool containers/tanks with water spray.**SECTION 6. ACCIDENTAL RELEASE MEASURES**

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Wear suitable protective equipment.

Spill Cleanup : Contain spill. Soak up with inert absorbent material. Collect and contain contaminated absorbent and dike material for disposal. Keep in suitable, closed containers for disposal. Ventilate the area. Clean contaminated surface thoroughly.

Accidental Release Measures : Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Clean contaminated floors and objects thoroughly while observing environmental regulations.
Dispose of in accordance with local regulations.



ARTISTRITM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

SECTION 7. HANDLING AND STORAGE

- Handling (Personnel) : Avoid breathing vapours or mist. Keep away from heat and flame. Do not use in areas without adequate ventilation.
Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Contaminated work clothing should not be allowed out of the workplace. Remove contaminated clothing and protective equipment before entering eating areas. Remove and wash contaminated clothing before re-use.
- Handling (Physical Aspects) : Keep away from heat and sources of ignition. Avoid formation of aerosol.
- Storage : Store at room temperature in the original container. Keep away from sources of ignition - No smoking. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. Keep container closed when not in use. Do not reuse empty container.
Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering controls : Local exhaust or a laboratory hood should be used when handling the materials. Maintain air concentrations below occupational exposure standards.
- Personal protective equipment
 - Respiratory protection : Provide adequate ventilation.
 - Hand protection : Material: Impervious gloves
 - Eye protection : Wear safety glasses with side shields.

Exposure Guidelines
Exposure Limit Values

Ethane-1,2-diol			
TLV	(ACGIH)	100 mg/m3	TLV-C Aerosol.
AEL *	(DUPONT)	10 mg/m3	8 & 12 hr. TWA Particulate.


ARTISTRTM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

AEL *	(DUPONT)	50 ppm	8 & 12 hr. TWA Vapor.
Alkyl ether AEL *	(DUPONT)	10 mg/m3	8 & 12 hr. TWA Aerosol.
AEL *	(DUPONT)	100 ppm	8 & 12 hr. TWA Vapor.
Carbon black Permissible exposure limit:	(OSHA)	3.5 mg/m3	8 hr. TWA
TLV	(ACGIH)	3 mg/m3	TWA Inhalable fraction.
AEL *	(DUPONT)	0.5 mg/m3 Hydrocarbons (PAH) < 0.1%	8 & 12 hr. TWA Polynuclear Aromatic
Cyclic amide AEL *	(DUPONT)	5 ppm	8 & 12 hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid
Color	: black
Odor	: not significant
pH	: 7 - 9
Boiling point	: 100 °C (212 °F)
Evaporation rate	: Slower than Ether

SECTION 10. STABILITY AND REACTIVITY



ARTISTRITM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

- Stability : No decomposition if stored normally.
- Conditions to avoid : None reasonably foreseeable.
- Incompatibility : Oxidizing agents Strong acids, alkaline substances
- Hazardous decomposition products : Under fire conditions:, formaldehyde-like

SECTION 11. TOXICOLOGICAL INFORMATION

- Ethane-1,2-diol
 - Dermal LD50 : > 3,500 mg/kg , Mouse
 - Oral LD50 : 1,650 mg/kg , Cat
 - Inhalation : no data available
 - Skin irritation : No skin irritation, Rabbit
 - Eye irritation : No eye irritation, Rabbit
 - Skin sensitization : Does not cause skin sensitisation., human
 - Repeated dose toxicity : Oral
Rat

Target Organs: Kidney
Kidney damage
 - Carcinogenicity : Not classifiable as a human carcinogen.
Animal testing did not show any carcinogenic effects.
 - Mutagenicity : Animal testing did not show any mutagenic effects.
Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
 - Reproductive toxicity : No toxicity to reproduction
No effects on or via lactation
Animal testing showed no reproductive toxicity.
 - Teratogenicity : Evidence suggests the substance is not a developmental toxin in animals.

Alkyl ether


ARTISTRITM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

Dermal LD50	:	13,300 mg/kg , Rabbit
Oral LD50	:	20,760 mg/kg , Rat
Inhalation 4 h LC50	:	> 48.1 mg/l , Rat
Inhalation 4 h Acute toxicity estimate	:	> 5 mg/l , Rat
Skin irritation	:	slight irritation, Rabbit
Eye irritation	:	slight irritation, Rabbit
Skin sensitization	:	Did not cause sensitisation on laboratory animals., Guinea pig Patch test on human volunteers did not demonstrate sensitisation properties., human
Repeated dose toxicity	:	Oral multiple species Oxylate crystal deposition
Carcinogenicity	:	Not classifiable as a human carcinogen.
Mutagenicity	:	Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Animal testing did not show any mutagenic effects.
Reproductive toxicity	:	No toxicity to reproduction Animal testing showed no reproductive toxicity.
Teratogenicity	:	Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.
Carbon black		
Oral LD50	:	> 8,000 mg/kg , Rat
Skin irritation	:	slight irritation, Rabbit
Eye irritation	:	Slight or no eye irritation, Rabbit
Carcinogenicity	:	Not classifiable as a human carcinogen. Overall weight of evidence indicates that the substance is not carcinogenic.


ARTISTRTM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

Mutagenicity : Animal testing did not show any mutagenic effects.
Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Cyclic amide

Dermal LD50 : > 2,000 mg/kg , Rat

Oral LD50 : 8,000 mg/kg , Rat

Inhalation : Rat
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Skin irritation : No skin irritation, Rabbit

Eye irritation : Eye irritation, Rabbit

Skin sensitization : Does not cause skin sensitisation., Mouse
Information given is based on data obtained from similar substances.

Repeated dose toxicity : Oral
Rat

Kidney effects

Mutagenicity : Animal testing did not show any mutagenic effects.
Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Reproductive toxicity : No toxicity to reproduction
Animal testing showed no reproductive toxicity.

Teratogenicity : Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity
Ethane-1,2-diol

96 h LC50 : Pimephales promelas (fathead minnow) 72,860 mg/l


ARTISTRITM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

96 h ErC50 : Pseudokirchneriella subcapitata (green algae) 6,500 mg/l
 48 h EC50 : Daphnia magna (Water flea) > 100 mg/l OECD Test Guideline 202

Alkyl ether

96 h LC50 : Pimephales promelas (fathead minnow) 75,200 mg/l
 48 h LC50 : Leuciscus idus (Golden orfe) > 10,000 mg/l
 24 h EC50 : Daphnia magna (Water flea) > 10,000 mg/l

Carbon black

96 h LC50 : Zebra fish > 1,000 mg/l OECD Test Guideline 203
 72 h EC50 : Algae > 10,000 mg/l
 24 h EC50 : Daphnia magna (Water flea) > 5,600 mg/l OECD Test Guideline 202

Cyclic amide

72 h ErC50 : Desmodesmus subspicatus (green algae) > 500 mg/l
 48 h EC50 : Daphnia magna (Water flea) > 500 mg/l Directive 67/548/EEC, Annex V, C.2.

Environmental Fate

Ethane-1,2-diol

Biodegradability : Readily biodegradable. 90 - 100 % OECD Test Guideline 301
 Bioaccumulation : Bioaccumulation is unlikely.

Alkyl ether

Biodegradability : 90 %
 Readily biodegradable.
 Bioaccumulation : Bioconcentration factor (BCF) : 10 - 180
 Bioaccumulation is unlikely.

Carbon black

Biodegradability : Product is not expected to be biodegradable.
 Bioaccumulation : Bioaccumulation is unlikely.

Cyclic amide



ARTISTRITM P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

Biodegradability : Biodegradable
Readily biodegradable.

Bioaccumulation : Bioaccumulation is unlikely.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : If recycling is not practicable, dispose of in compliance with local regulations. Never place unused product down any indoor or out door drain.

Container disposal: : Do not reuse empty container. Contaminated/not cleaned containers should be treated/handled like product waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and Federal Regulations, as well as industry Standards.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA : On the inventory, or in compliance with the inventory

SARA 313 Regulated Chemical(s) : Ethane-1,2-diol

CERCLA Reportable Quantity : 51605 lbs
Based on the percentage composition of this chemical in the product.:
Ethane-1,2-diol

California Prop. 65 : WARNING! This product contains a chemical or chemicals known to the State



ARTISTRI™ P5400+ BLACK TEXTILE INK

Version 2.0

Revision Date 12/10/2014

Ref. 130000129166

of California to cause cancer.

PA Right to Know Regulated Chemical(s) : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): Ethane-1,2-diol, Alkyl ether, Carbon black, Cyclic amide

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): Ethane-1,2-diol, Carbon black

SECTION 16. OTHER INFORMATION

The DuPont Oval Logo is a registered trademark of E.I. du Pont de Nemours and Company.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.