

ARTISTRI® P5400+ BLACK TEXTILE INK

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ARTISTRI® P5400+ BLACK TEXTILE INK
Product Use : Printing ink

Restrictions on use : Do not use product for anything outside of the above specified uses.
Manufacturer/Supplier : DuPont
974 Centre Road
Wilmington, DE 19805, USA

Product Information : 1-302-774-1000
Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)
Transport Emergency : CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION**Product hazard category**

Specific target organ toxicity - repeated exposure Category 2

Label content

Pictogram :



Signal word : Warning

**ARTISTRI® P5400+ BLACK TEXTILE INK**

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

Hazardous warnings : May cause damage to organs through prolonged or repeated exposure.
(Kidney)

Hazardous prevention : Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
measures Get medical advice/ attention if you feel unwell.
Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 20.9323 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Ethane-1,2-diol	107-21-1	5 - 10 %
2-Pyrrolidone	616-45-5	1 - 5 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

**ARTISTRI® P5400+ BLACK TEXTILE INK**

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

General advice	: Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.
Inhalation	: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If breathing is irregular or stopped, administer artificial respiration. Get medical attention.
Skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
Eye contact	: In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical advice/attention.
Ingestion	: If swallowed, call a poison control centre or doctor immediately. Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Most important symptoms/effects, acute and delayed	: No applicable data available.
Protection of first-aiders	: No applicable data available.
Notes to physician	: No specific intervention is indicated. Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray, Dry chemical, Carbon dioxide (CO ₂)
Unsuitable extinguishing media	: No applicable data available.
Specific hazards	: Hazardous decomposition products formed under fire conditions. (see also section 10) Avoid breathing decomposition products.
Special protective equipment for firefighters	: Exposure to decomposition products may be a hazard to health. Wear self-contained breathing apparatus for firefighting if necessary.



ARTISTRI® P5400+ BLACK TEXTILE INK

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

Further information : Evacuate personnel to safe areas. Stop spill/release if it can be done with minimal risk. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Wear suitable protective equipment.

Environmental precautions : Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Clean contaminated floors and objects thoroughly while observing environmental regulations.

Spill Cleanup : Contain spill. Soak up with inert absorbent material. Collect and contain contaminated absorbent and dike material for disposal. Keep in suitable, closed containers for disposal. Ventilate the area. Clean contaminated floors and objects thoroughly while observing environmental regulations.

Accidental Release Measures : Dispose of in accordance with local regulations.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel) : Avoid inhalation, ingestion and contact with skin and eyes. Do not use in areas without adequate ventilation. For personal protection see section "Exposure controls/personal protection"
 Handle in accordance with good industrial hygiene and safety practice. Keep container closed. Keep away from food and drink. Wash hands before eating, drinking, or smoking. Remove contaminated clothing and protective equipment before entering eating areas. Wash contaminated clothing before re-use.

Handling (Physical Aspects) : Normal measures for preventive fire protection.

Dust explosion class : No applicable data available.
 Storage : Keep containers tightly closed in a cool, well-ventilated place. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. Do not reuse empty container.

**ARTISTRI® P5400+ BLACK TEXTILE INK**

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

Stable under normal conditions.

Storage period : No applicable data available.

Storage temperature : No applicable data available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Ensure adequate ventilation. Maintain air concentrations below occupational exposure standards. General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable limits.

Personal protective equipment
Respiratory protection : No personal respiratory protective equipment normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

Hand protection : Material: Impervious gloves
Additional protection: Gloves must be inspected prior to use., Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough., The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other., The exact break through time can be obtained from the protective glove producer and this has to be observed., Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Wear safety glasses or coverall chemical splash goggles.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Lightweight protective clothing and safety shoes are recommended.

Exposure Guidelines
Exposure Limit Values


ARTISTRI® P5400+ BLACK TEXTILE INK

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

Ethane-1,2-diol TLV	(ACGIH)	100 mg/m3	TLV-C Aerosol.
AEL *	(DuPont)	10 mg/m3	8 & 12 hr. TWA Particulate.
AEL *	(DuPont)	50 ppm	8 & 12 hr. TWA Vapor.
2-Pyrrolidone AEL *	(DuPont)	5 ppm	8 & 12 hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : liquid
Form : liquid
Color : black

Odor : not significant

Odor threshold : No applicable data available.

pH : 7 - 9

Melting point/range : No applicable data available.

Boiling point/boiling range : Boiling point
100 °C (212 °F)

Flash point : > 93 °C

Evaporation rate : Slower than Ether

Flammability (solid, gas) : No applicable data available.

Upper explosion limit : No applicable data available.

Lower explosion limit : No applicable data available.

**ARTISTRI® P5400+ BLACK TEXTILE INK**

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

Vapour Pressure	: No applicable data available.
Vapour density	: No applicable data available.
Specific gravity (Relative density)	: No applicable data available.
Water solubility	: No applicable data available.
Solubility(ies)	: No applicable data available.
Partition coefficient: n-octanol/water	: No applicable data available.
Auto-ignition temperature	: No applicable data available.
Decomposition temperature	: No applicable data available.
Viscosity, kinematic	: No applicable data available.
Viscosity, dynamic	: No applicable data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable under recommended conditions of storage, use and temperature. Stable at normal temperatures and storage conditions.
Possibility of hazardous reactions	: None reasonably foreseeable.
Conditions to avoid	: Avoid extreme heat. Do not freeze.
Incompatible materials	: Acids, bases and strong oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed. Under fire conditions:, Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Formaldehyde

**ARTISTRI® P5400+ BLACK TEXTILE INK**

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

SECTION 11. TOXICOLOGICAL INFORMATION**ARTISTRI® P5400+ BLACK TEXTILE INK**

Further information : There is no data available for this product.

Ethane-1,2-diol

Inhalation : no data available

Dermal LD50 : > 3,500 mg/kg , Mouse

Oral LD50 : 1,650 mg/kg , Cat

Skin irritation : No skin irritation, Rabbit

Eye irritation : No eye irritation, Rabbit

Skin sensitization : Does not cause skin sensitisation., human

Repeated dose toxicity : Oral
Rat-
Target Organs: Kidney
Kidney damageCarcinogenicity : Not classifiable as a human carcinogen.
Animal testing did not show any carcinogenic effects.Mutagenicity : Animal testing did not show any mutagenic effects.
Tests on bacterial or mammalian cell cultures did not show mutagenic effects.Reproductive toxicity : No toxicity to reproduction
No effects on or via lactation
Animal testing showed no reproductive toxicity.

Teratogenicity : Evidence suggests the substance is not a developmental toxin in animals.

2-PyrrolidoneInhalation : Rat
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.


ARTISTRI® P5400+ BLACK TEXTILE INK

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

Dermal LD50	:	> 2,000 mg/kg , Rat
Oral LD50	:	8,000 mg/kg , Rat
Skin irritation	:	No skin irritation, Rabbit
Eye irritation	:	Eye irritation, Rabbit
Skin sensitization	:	Does not cause skin sensitisation., Mouse Information given is based on data obtained from similar substances.
Repeated dose toxicity	:	Oral Rat - NOAEL: 207 mg/kg Method: OECD Test Guideline 408 Kidney effects
Mutagenicity	:	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Reproductive toxicity	:	No toxicity to reproduction Animal testing showed no reproductive toxicity.
Teratogenicity	:	Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.

Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

Material	IARC	NTP	OSHA
Carbon black	2B		
Carbon black	2B		


ARTISTRI® P5400+ BLACK TEXTILE INK

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Ethane-1,2-diol

- 96 h LC50 : Pimephales promelas (fathead minnow) 72,860 mg/l
- 96 h ErC50 : Pseudokirchneriella subcapitata (green algae) 6,500 mg/l
- 48 h EC50 : Daphnia magna (Water flea) > 100 mg/l OECD Test Guideline 202

2-Pyrrolidone

- 72 h ErC50 : Desmodesmus subspicatus (green algae) > 500 mg/l
- 48 h EC50 : Daphnia magna (Water flea) > 500 mg/l Directive 67/548/EEC, Annex V, C.2.

Environmental Fate

Ethane-1,2-diol

- Biodegradability : Readily biodegradable. 90 - 100 % OECD Test Guideline 301
- Bioaccumulation : Bioaccumulation is unlikely.

2-Pyrrolidone

- Biodegradability : Biodegradable
Readily biodegradable.

- Bioaccumulation : Bioaccumulation is unlikely.

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal methods - Product : If recycling is not practicable, dispose of in compliance with local regulations. Never place unused product down any indoor or out door drain.

Waste disposal methods - Container : Do not reuse empty container. Contaminated/not cleaned containers should be treated/handled like product waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and Federal Regulations, as well


ARTISTRI® P5400+ BLACK TEXTILE INK

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

as industry Standards.

Contaminated packaging : No applicable data available.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

Regulated by DOT/49CFR as Combustible Liquid when transported in a bulk package (≥ 119 gallons(450 litres)).
SECTION 15. REGULATORY INFORMATION

TSCA : On the inventory, or in compliance with the inventory

SARA 313 Regulated Chemical(s) : Ethane-1,2-diol

PA Right to Know Regulated Chemical(s) : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): Ethane-1,2-diol, Alkyl ether, Carbon black, 2-Pyrrolidone

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): Ethane-1,2-diol, Carbon black

CERCLA Reportable Quantity : 51605 lbs
Based on the percentage composition of this chemical in the product.: Ethane-1,2-diolCalifornia Prop. 65 : WARNING! This product contains a chemical or chemicals known to the State of California to cause cancer.
WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.



ARTISTRI® P5400+ BLACK TEXTILE INK

Version 3.1

Revision Date 01/30/2017

Ref. 130000129166

SECTION 16. OTHER INFORMATION

The DuPont Oval Logo, DuPont™ and all products denoted with ® or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.

Revision Date : 01/30/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.