

Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name ARTISTRI® P5910 WHITE TEXTILE INK

Product Use : Printing ink

Do not use product for anything outside of the above specified uses. Restrictions on use

Manufacturer/Supplier DuPont

974 Centre Road

Wilmington, DE 19805, USA

 Product Information
 : 1-302-774-1000

 Medical Emergency
 : 1-800-441-3637 (outside the U.S. 1-302-774-1139)

 Transport Emergency
 : CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Product hazard category

Specific target organ toxicity -Category 2

repeated exposure

Label content

Pictogram



Signal word : Warning

Safety Data Sheet



ARTISTRI® P5910 WHITE TEXTILE INK

Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Hazardous warnings : May cause damage to organs through prolonged or repeated exposure.

Hazardous prevention

measures

: Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Get medical advice/ attention if you feel unwell.

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 32.1015 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Ethane-1,2-diol	107-21-1	10 - 20 %
Titanium dioxide	13463-67-7	<15 %
Humectant		<10 %
Non regulated ingredients		>45%

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

SECTION 4. FIRST AID MEASURES

General advice : Never give anything by mouth to an unconscious person. When symptoms

persist or in all cases of doubt seek medical advice.

Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If breathing

is irregular or stopped, administer artificial respiration. Get medical attention.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15

minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before

re-use.

Eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty

of water, also under the eyelids, for at least 15 minutes. Get medical advice/

attention.

Ingestion : If swallowed, call a poison control centre or doctor immediately. Rinse mouth

with water. DO NOT induce vomiting unless directed to do so by a physician or

poison control center.

Most important

symptoms/effects, acute

and delayed

Protection of first-aiders

Notes to physician

: No applicable data available.

: No applicable data available.

: No specific intervention is indicated. Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

Water spray, Dry chemical, Carbon dioxide (CO2)

Unsuitable extinguishing

media

: No applicable data available.

Specific hazards : Hazardous decomposition products formed under fire conditions. (see also

section 10) Avoid breathing decomposition products.



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Special protective equipment

for firefighters

: Exposure to decomposition products may be a hazard to health. Wear self-

contained breathing apparatus for firefighting if necessary.

Further information : Evacuate personnel to safe areas. Stop spill/release if it can be done with

minimal risk. Do not allow run-off from fire fighting to enter drains or water

courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Wear

suitable protective equipment.

Environmental precautions : Prevent further leakage or spillage if safe to do so. Prevent product from

entering drains. Clean contaminated floors and objects thoroughly while

observing environmental regulations.

Spill Cleanup : Contain spill. Soak up with inert absorbent material. Collect and contain

contaminated absorbent and dike material for disposal. Keep in suitable, closed containers for disposal. Ventilate the area. Clean contaminated floors

and objects thoroughly while observing environmental regulations.

Accidental Release Measures : Dispose of in accordance with local regulations.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel) : Avoid inhalation, ingestion and contact with skin and eyes. Do not use in

areas without adequate ventilation. For personal protection see section

"Exposure controls/personal protection"

Handle in accordance with good industrial hygiene and safety practice. Keep container closed. Keep away from food and drink. Wash hands before eating,

drinking, or smoking. Remove contaminated clothing and protective

equipment before entering eating areas. Wash contaminated clothing before

re-use.

Handling (Physical Aspects) : Normal measures for preventive fire protection.



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Dust explosion class

: No applicable data available.

Storage

: Keep containers tightly closed in a cool, well-ventilated place. Do not store or

consume food, drink or tobacco in areas where they may become contaminated with this material. Do not reuse empty container.

Stable under normal conditions.

Storage period : No applicable data available.

Storage temperature : No applicable data available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Ensure adequate ventilation. Maintain air concentrations below occupational

exposure standards. General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable

limits.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required. When

workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe

respirator use limitations specified by the manufacturer.

Hand protection : Material: Impervious gloves

Additional protection: Gloves must be inspected prior to use., Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough., The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other., The exact break through time can be obtained from the protective glove producer and this has to be observed., Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger

of cuts, abrasion, and the contact time.

Eye protection : Wear safety glasses or coverall chemical splash goggles.

Skin and body protection : Choose body protection in relation to its type, to the concentration and

amount of dangerous substances, and to the specific work-place. Lightweight protective clothing and safety shoes are recommended.

Exposure Guidelines



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Exposure Limit Values

Ethane-1,2-diol

TLV (ACGIH) 100 mg/m3 TLV-C Aerosol.

AEL * (DuPont) 10 mg/m3 8 & 12 hr. TWA Particulate.

AEL * (DuPont) 50 ppm 8 & 12 hr. TWA Vapor.

Titanium dioxide

Permissible (OSHA) 15 mg/m3 8 hr. TWA Total dust.

exposure limit:

TLV (ACGIH) 10 mg/m3 TWA

AEL * (DuPont) 10 mg/m3 8 & 12 hr. TWA Total dust.

AEL * (DuPont) 5 mg/m3 8 & 12 hr. TWA Respirable dust.

Humectant

Permissible (OSHA) 5 mg/m3 8 hr. TWA Respirable fraction.

exposure limit:

Permissible (OSHA) 15 mg/m3 8 hr. TWA Total dust.

exposure limit:

Non regulated ingredients

No applicable data available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : liquid Form : liquid

^{*} AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Color : white

Odor : not significant

Odor threshold : No applicable data available.

pH : 6-9

Melting point/freezing point : Freezing point

-13 °C (9 °F)

Boiling point/boiling range : Boiling point

100 °C (212 °F)

Flash point : 100 °C

Evaporation rate : Slower than Ether

Flammability (solid, gas) : No applicable data available.

Upper explosion limit : 15.3 vol%

Lower explosion limit : 3.2 vol%

Vapor pressure : 1.0 hPa

Vapour density : No applicable data available.

Specific gravity (Relative

density)

: 1.12

Water solubility : soluble

Solubility(ies) : No applicable data available.

Partition coefficient: n-

octanol/water

: No applicable data available.

Auto-ignition temperature : No applicable data available.

Ignition temperature : 401 °C

Decomposition temperature : No applicable data available.



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Viscosity, kinematic : No applicable data available.

Viscosity, dynamic : No applicable data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable under recommended conditions of storage,

use and temperature.

Stable at normal temperatures and storage conditions.

Possibility of hazardous

reactions

: None reasonably foreseeable.

Conditions to avoid : Avoid extreme heat. Do not freeze.

Incompatible materials : Acids, bases and strong oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

Under fire conditions:, Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

ARTISTRI® P5910 WHITE TEXTILE INK

Further information : There is no data available for this product.

Ethane-1,2-diol

Inhalation : no data available

Dermal LD50 : > 3,500 mg/kg, Mouse

Oral LD50 : 1,650 mg/kg , Cat

Skin irritation : No skin irritation, Rabbit

Eye irritation : No eye irritation, Rabbit

Skin sensitization : Does not cause skin sensitisation., human

Repeated dose toxicity : Oral

Rat



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Target Organs: Kidney

Kidney damage

Carcinogenicity : Not classifiable as a human carcinogen.

Animal testing did not show any carcinogenic effects.

Mutagenicity : Animal testing did not show any mutagenic effects.

Tests on bacterial or mammalian cell cultures did not show mutagenic

effects.

Reproductive toxicity : No toxicity to reproduction

No effects on or via lactation

Animal testing showed no reproductive toxicity.

Teratogenicity : Evidence suggests the substance is not a developmental toxin in

animals.

Titanium dioxide

Inhalation 4 h LC50 : > 6.82 mg/l, Rat

Dermal LD50 : > 10,000 mg/kg , Rabbit

Oral LD50 : > 5,000 mg/kg , Rat

Skin irritation : No skin irritation, Rabbit

Eye irritation : No eye irritation, Rabbit

Skin sensitization : Does not cause skin sensitisation., Guinea pig

Does not cause respiratory sensitisation., Mouse

Repeated dose toxicity : Oral

Rat

_

NOAEL: 1,000 mg/kgMethod: OECD Test Guideline 408

No toxicologically significant effects were found.

Carcinogenicity : Not classifiable as a human carcinogen.

Overall weight of evidence indicates that the substance is not

carcinogenic.

Mutagenicity : Animal testing did not show any mutagenic effects.

Tests on bacterial or mammalian cell cultures did not show mutagenic



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

effects.

Reproductive toxicity : Animal testing showed no reproductive toxicity.

Teratogenicity : Animal testing showed no developmental toxicity.

Humectant

Dermal LD50 : 56,750 mg/kg, Guinea pig

Oral LD50 : 27,260 mg/kg , Rat

Skin irritation : No skin irritation, Rabbit

Eye irritation : No eye irritation, Rabbit

Skin sensitization : Does not cause skin sensitisation., human

Repeated dose toxicity : Oral

Rat

NOAEL: 8,000 mg/kg

No toxicologically significant effects were found.

Carcinogenicity : Not classifiable as a human carcinogen.

Animal testing did not show any carcinogenic effects.

Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic

effects.

Reproductive toxicity : No toxicity to reproduction

Animal testing showed no reproductive toxicity.

Teratogenicity : Animal testing showed no developmental toxicity.

Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

Material IARC NTP OSHA



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Titanium dioxide 2B

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity Ethane-1,2-diol

96 h LC50 : Pimephales promelas (fathead minnow) 72,860 mg/l

96 h ErC50 : Pseudokirchneriella subcapitata (green algae) 6,500 mg/l

48 h EC50 : Daphnia magna (Water flea) > 100 mg/l OECD Test Guideline 202

Titanium dioxide

96 h LC50 : Pimephales promelas (fathead minnow) > 1,000 mg/l

72 h ErC50 : Pseudokirchneriella subcapitata (green algae) > 100 mg/l see user

defined free text

72 h NOEC : Algae 5,600 mg/l see user defined free text

48 h EC50 : Daphnia magna (Water flea) > 100 mg/l OECD Test Guideline 202

Humectant

96 h LC50 : Oncorhynchus mykiss (rainbow trout) 54,000 mg/l

ErC50

48 h EC50 : Daphnia magna (Water flea) 1,955 mg/l

Environmental Fate

Ethane-1,2-diol

Biodegradability : Readily biodegradable. 90 - 100 % OECD Test Guideline 301

Bioaccumulation : Bioaccumulation is unlikely.

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal methods - : If recycling is not practicable, dispose of in compliance with local regulations.

Product Never place unused product down any indoor or out door drain.



Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

Waste disposal methods -

Container

: Do not reuse empty container.

Contaminated/not cleaned containers should be treated/handled like product

waste.

Dispose of container properly.

Refer to applicable Local, State/Provincial, and Federal Regulations, as well

as industry Standards.

Contaminated packaging : No applicable data available.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA : On the inventory, or in compliance with the inventory

SARA 313 Regulated

Chemical(s)

: Ethane-1,2-diol

PA Right to Know

Regulated Chemical(s)

: Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances):

Ethane-1,2-diol, Titanium dioxide, Humectant

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List present

at a concentration of 1% or more (0.1% for substances identified as

carcinogens, mutagens or teratogens): Ethane-1,2-diol, Titanium dioxide,

Humectant

California Prop. 65 : WARNING! This product contains a chemical or chemicals known to the State

of California to cause cancer.

WARNING! This product contains a chemical known to the State of California

to cause birth defects or other reproductive harm.

Safety Data Sheet



ARTISTRI® P5910 WHITE TEXTILE INK

Version 3.0

Revision Date 09/20/2016 Ref. 130000129461

SECTION 16. OTHER INFORMATION

The DuPont Oval Logo, $DuPont^{\mathsf{TM}}$ and all products denoted with $^{\mathsf{R}}$ or $^{\mathsf{TM}}$ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.

Revision Date : 09/20/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.