

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018  
Revision Date : 08/27/2018

Ref. 130000138911

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : M-DTG-K-1L  
Product Use : Printing ink

Restrictions on use : Do not use product for anything outside of the above specified uses.  
Manufacturer/Supplier : The M&R Companies Telephone: +(800) 736-6431  
440 Medinah Road  
Roselle, IL 60172, U.S.A

Emergency : For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire,  
Telephone Number : Exposure, or Accident Call Chemtrec -Emergency Number(s): Within US  
and Canada: +1 (800) 424-9300 Outside US and Canada: +1 (703)741-5970

**SECTION 2. HAZARDS IDENTIFICATION****Product hazard category**

Specific target organ toxicity - Category 2  
repeated exposure

**Label content**

Pictogram :



Signal word : Warning

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018 Ref. 130000138911  
Revision Date : 08/27/2018

Hazardous warnings : May cause damage to organs through prolonged or repeated exposure.  
(Kidney)

Hazardous prevention : Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
measures Get medical advice/ attention if you feel unwell.  
Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 40 - 50 %

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No.	Concentration
Ethane-1,2-diol	107-21-1	1 - 5 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**SECTION 4. FIRST AID MEASURES**

General advice : Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.

Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If breathing is irregular or stopped, administer artificial respiration. Get medical attention.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018 Ref. 130000138911  
Revision Date : 08/27/2018

Eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical advice/attention.

Ingestion : If swallowed, call a poison control centre or doctor immediately. Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center.

Most important symptoms/effects, acute and delayed : No applicable data available.

Protection of first-aiders : No applicable data available.

Notes to physician : No specific intervention is indicated. Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray, Dry chemical, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : No applicable data available.

Specific hazards : Hazardous decomposition products formed under fire conditions. (see also section 10) Avoid breathing decomposition products.

Special protective equipment for firefighters : Exposure to decomposition products may be a hazard to health. Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Evacuate personnel to safe areas. Stop spill/release if it can be done with minimal risk. Do not allow run-off from fire fighting to enter drains or water courses.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018 Ref. 130000138911  
Revision Date : 08/27/2018

- Safeguards (Personnel) : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Wear suitable protective equipment.
- Environmental precautions : Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Clean contaminated floors and objects thoroughly while observing environmental regulations.
- Spill Cleanup : Contain spill. Soak up with inert absorbent material. Collect and contain contaminated absorbent and dike material for disposal. Keep in suitable, closed containers for disposal. Ventilate the area. Clean contaminated floors and objects thoroughly while observing environmental regulations.
- Accidental Release Measures : Dispose of in accordance with local regulations.

**SECTION 7. HANDLING AND STORAGE**

- Handling (Personnel) : Avoid inhalation, ingestion and contact with skin and eyes. Do not use in areas without adequate ventilation. For personal protection see section "Exposure controls/personal protection"  
Handle in accordance with good industrial hygiene and safety practice. Keep container closed. Keep away from food and drink. Wash hands before eating, drinking, or smoking. Remove contaminated clothing and protective equipment before entering eating areas. Wash contaminated clothing before re-use.
- Handling (Physical Aspects) : Normal measures for preventive fire protection.
- Dust explosion class : No applicable data available.
- Storage : Keep containers tightly closed in a cool, well-ventilated place. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. Do not reuse empty container.  
Stable under normal conditions.
- Storage period : No applicable data available.
- Storage temperature : No applicable data available.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Engineering controls : Ensure adequate ventilation. Maintain air concentrations below occupational

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018  
Revision Date : 08/27/2018

Ref. 130000138911

exposure standards. General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable limits.

## Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

Hand protection : Material: Impervious gloves  
Additional protection: Gloves must be inspected prior to use., Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough., The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other., The exact break through time can be obtained from the protective glove producer and this has to be observed., Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Wear safety glasses or coverall chemical splash goggles.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.  
Lightweight protective clothing and safety shoes are recommended.

## Exposure Guidelines

## Exposure Limit Values

<b>Ethane-1,2-diol</b>			
TLV	(ACGIH)	25 ppm	TWA
TLV	(ACGIH)	50 ppm	STEL
TLV	(ACGIH)	10 mg/m3	STEL
AEL *	(DuPont)	10 mg/m3	8 & 12 hr. TWA
AEL *	(DuPont)	50 ppm	8 & 12 hr. TWA

\* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018  
Revision Date : 08/27/2018

Ref. 130000138911

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

## Appearance

Physical state : liquid  
Form : liquid  
Color : black

Odor : characteristic

Odor threshold : No applicable data available.

pH : 8.2

Melting point/range : No applicable data available.

Boiling point/boiling range : Boiling point  
no data available

Flash point : > 94 °C  
Method: Pensky-Martens closed cup - PMCC

Evaporation rate : No applicable data available.

Flammability (solid, gas) : No applicable data available.

Upper explosion limit : No applicable data available.

Lower explosion limit : No applicable data available.

Vapour Pressure : No applicable data available.

Vapour density : No applicable data available.

Density : 1.087 g/cm<sup>3</sup>

Specific gravity (Relative density) : No applicable data available.

Water solubility : soluble

Solubility(ies) : No applicable data available.

Partition coefficient: n- : No applicable data available.

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018 Ref. 130000138911  
Revision Date : 08/27/2018

octanol/water

Auto-ignition temperature : No applicable data available.

Decomposition temperature : No applicable data available.

Viscosity, kinematic : No applicable data available.

Viscosity, dynamic : 12 mPa.s at 25 °C (77 °F)

% Volatile : 81 %

Volatile organic content  
(VOC) : 0.74 kg/l**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable under recommended conditions of storage,  
use and temperature.  
Stable at normal temperatures and storage conditions.Possibility of hazardous  
reactions : None reasonably foreseeable.

Conditions to avoid : Avoid extreme heat. Do not freeze.

Incompatible materials : Acids, bases and strong oxidizing agents

Hazardous decomposition  
products : No decomposition if stored and applied as directed.  
Under fire conditions:, Carbon monoxide, carbon dioxide and unburned  
hydrocarbons (smoke).**SECTION 11. TOXICOLOGICAL INFORMATION**

M-DTG-K-1L

Further information : There is no data available for this product.

Ethane-1,2-diol

Inhalation : no data available

Inhalation :

Dermal LD50 : &gt; 3,500 mg/kg , Mouse

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018  
Revision Date : 08/27/2018

Ref. 130000138911

Oral LD50 : 1,650 mg/kg , Cat

Skin irritation : No skin irritation, Rabbit

Eye irritation : No eye irritation, Rabbit

Skin sensitization : Does not cause skin sensitisation., human

Repeated dose toxicity : Oral  
Rat  
-  
Target Organs: Kidney  
Kidney damage

Carcinogenicity : Not classifiable as a human carcinogen.  
Animal testing did not show any carcinogenic effects.

Mutagenicity : Animal testing did not show any mutagenic effects.  
Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Reproductive toxicity : No toxicity to reproduction  
No effects on or via lactation  
Animal testing showed no reproductive toxicity.

Teratogenicity : Evidence suggests the substance is not a developmental toxin in animals.

**Carcinogenicity**

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

Material	IARC	NTP	OSHA
Carbon black	2B		

**SECTION 12. ECOLOGICAL INFORMATION**

Aquatic Toxicity



**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018  
Revision Date : 08/27/2018

Ref. 130000138911

## Ethane-1,2-diol

96 h LC50 : Pimephales promelas (fathead minnow) 72,860 mg/l  
96 h ErC50 : Pseudokirchneriella subcapitata (green algae) 6,500 mg/l  
48 h EC50 : Daphnia magna (Water flea) > 100 mg/l OECD Test Guideline 202

## Environmental Fate

## Ethane-1,2-diol

Biodegradability : Readily biodegradable. 90 - 100 % OECD Test Guideline 301

Bioaccumulation : Bioaccumulation is unlikely.

Additional ecological information : There is no data available for this product.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Waste disposal methods - Product : If recycling is not practicable, dispose of in compliance with local regulations.  
Never place unused product down any indoor or out door drain.

Waste disposal methods - Container : Do not reuse empty container.  
Contaminated/not cleaned containers should be treated/handled like product waste.  
Dispose of container properly.  
Refer to applicable Local, State/Provincial, and Federal Regulations, as well as industry Standards.

Contaminated packaging : No applicable data available.

**SECTION 14. TRANSPORT INFORMATION**

Not classified as dangerous in the meaning of transport regulations.

**SECTION 15. REGULATORY INFORMATION**

TSCA : On the inventory, or in compliance with the inventory

**M-DTG-K-1L**

Version 4.0

Issue Date : 09/01/2018  
Revision Date : 08/27/2018

Ref. 130000138911

SARA 311/312 Hazard classification : Specific target organ toxicity (single or repeated exposure)

SARA 313 Regulated Chemical(s) : Ethane-1,2-diol

California Prop. 65 : This product can expose you to Ethane-1,2-diol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SECTION 16. OTHER INFORMATION**

Issue Date : 09/01/2018  
Revision Date : 08/27/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.